

# Sinar SNR-42 series


## Dry Type

### TERMINAL BLOCK

#### A. POLYMER



#### B. BAKELITE



### SPECIFICATIONS

PHASE	: 1 Ø
FREQUENCY	: 50/60 Hz
PRIMARY VOLTAGE	: 400-440 V
SECONDARY VOLTAGE	: 200-220 V
CLASS OF INSULATION	: F
STANDARD	: JIS - C5310

Type	Capacity (VA)	Ampere (A)	Dimension (mm)						Weight (kg)
			L	W	H	Lp	Wp	φ A X B	
SNR30 - 42	30	0,30	88	82	98	58	60	4.5 X 10	1,2
SNR50 - 42	50	0,50	88	86	98	58	65	4.5 X 10	1,3
SNR75 - 42	75	0,75	88	91	98	58	75	4.5 X 10	1,8
SNR100 - 42	100	1,0	89	86	103	71	65	4.5 X 10	2,2
SNR150 - 42	150	1,5	89	92	103	71	70	4.5 X 10	2,5
SNR200 - 42	200	2,0	101	102	112	62	74	5.5 X 10	3,5
SNR300 - 42	300	3,0	117	115	122	81	76	7 X 14	4,8
SNR500 - 42	500	5,0	133	131	142	97	82	7 X 14	7,3
SNR750 - 42	750	7,5	152	135	156	113	94	7 X 14	9,6
SNR1K - 42	1K	10	159	152	163	110	101	7 X 14	10,3
SNR1.5K - 42	1.5K	15	177	165	182	120	118	8 X 16	14,9
SNR2K - 42	2K	20	177	190	190	120	145	8 X 16	20,0
SNR3K - 42	3K	30	177	215	190	120	172	8 X 16	24,7
SNR4K - 42	4K	40	230	230	291	180	165	10 X 25	42,0
SNR5K - 42	5K	50	230	257	291	180	190	10 X 25	48,0

